

Hydraulic Hose Line

Varied pressures, abrasion levels and temperatures are no match for Continental ContiTech Hydraulic Hoses.



3/16" - 2"

SR1SN

SAE 100R1AT/1SN

Hydraulic applications requiring 1-braid hose at higher EN/DIN pressures.



3/16" - 1 1/8"

Desert® DR5

SAE 100R5/SAE J1942

Medium pressure, high temperature blue textile cover reinforced with 1-braid steel wire.



1/4" - 2"

Desert® DR2SN

SAE 100R2AT/2SN

High temperature 2-braid hose at EN/DIN pressures.



3/16" - 1 13/16"

SR5

General purpose, medium pressure applications.



1/4" - 2"

Arctic® LR2SN

SAE 100R2AT/2SN

High pressure, low temperature hydraulic oil lines.



1/4" - 1 1/4"

SR3

SAE 100R3/EN 854 R3

Low pressure, 2 textile braid reinforced hose.



1/4" - 4"

HR4

SAE 100R4

Low pressure, high temperature return line or suction line.



1/8" - 1"

SR7

SAE 100R7/855 R7

Medium pressure, thermoplastic hose with a perforated cover.



3/16" - 1/2"

TR7

SAE 100R7 (Twin-Line)

Medium pressure, twin-line thermoplastic hose with a perforated cover.



1/8" - 1"

NR7

SAE 100R7 (Non-Conductive)

Medium pressure, thermoplastic hose with a non-perforated cover.



1/4" - 1/2"

BR7

SAE 100R7

(Twin-Line, Non-Conductive)
Medium pressure, twin-line thermoplastic hose with a non-perforated cover.



3/16" - 1/2"

SR8

SAE 100R8/855 R8

High pressure, thermoplastic hose with a perforated cover.



3/4" - 1/2"

TR8

SAE 100R8 (Twin-Line)
High pressure, twin-line, thermoplastic hose with a perforated cover.



1/4" - 1/2"

NR8

SAE 100R8 (Non-Conductive)
High pressure, thermoplastic hose with a non-perforated cover.



1/4" - 1"

S4SP

EN 856 4SP/DIN 20023 4SP
A 4-spiral hydraulic hose for very high pressure applications.



3/4" - 2"

S4SH

EN 856 4SH/DIN 20023 4SH
A 4-spiral hydraulic hose for very high pressure, pulsating applications.



3/8" - 2"

SR12


SAE 100R12/856 R12
A 4-spiral hydraulic hose for very high pressure applications subject to surges or flexing.



3/4" - 2"

SR13

SAE 100R13/856 R13
A 4- and 6-spiral hose for very high pressure applications subject to surges or flexing.



3/16" - 1"

SR14A

SAE 100R14A
PTFE line hose for air compressor discharge, hot oils and fluids, used under demanding physical conditions.



1/2" - 2"

SR15


SAE 100R15
A 4- and 6-spiral hose for severe high pressure applications.



1/4" - 1 1/4"

SR16SC

SAE 100R16/857 2SC
For high pressure service with tight bends exceeding SAE 100R2 and SAE 100R16 standards.



1/4" - 1"

Desert® DR16SC

SAE 100R16
High pressure 2-braid hose with excellent impulse performance and high flexibility.



1/4" - 1"

XR16SC

SAE 100R16/857 2SC
For high pressure service with tight bends requiring maximum abrasion resistance.



1/4" - 1"

XCP3

SAE 100R17
For high pressure hydraulic applications replacing SAE 100R17 with greater flexibility and superior abrasion resistance.



1/4" - 1/2"

SR18

SAE 100R18
Thermoplastic hose, highly flexible even in cold temperatures.



1/4" - 3/8"

SHJ

Jack Hose
For extreme high pressure hydraulic lines for jacking systems.



1/4" - 1"

Insta-Grip™ 300

Push-On
For use with push-on fittings, 300 psi and applications requiring non-conductivity.



5/16" - 3/4"

Galaxy® 4890, 4826, 4867

Air Conditioning Hose
For AC applications requiring Cool Clip™ or Cool Crimp™ fittings.